

**RECEIVED  
CENTRAL FAX CENTER****APR 03 2007**IN THE CLAIMS

1. (Currently Amended) A computer-implemented method comprising:  
fixing a logical identifier for a signal line at an input port of an egress time slot interchange (ETSI) of an egress interface of a line card of a network element, the ETSI having a plurality of input ports, each having a signal line;  
mapping via a translation module coupled to the ETSI a first physical identifier for a first physical signal line to the logical identifier; and  
the translation module remapping a second physical identifier for a second physical signal line to the logical identifier responsive to a line failure on the first physical signal line.
2. (Original) The method of claim 1 wherein mapping comprises:  
writing to a cross connect table and wherein remapping comprises rewriting the cross connect table.
3. (Original) The method of claim 1 further comprising:  
switching a signal from a second physical signal line to a physical line corresponding to the logical identifier responsive to the remapping.
4. (Original) The method of claim 1 wherein fixing comprises:  
assigning an identifier to each port of the egress interface during initialization; and  
preventing change to the identifier after initialization.

5. (Original) The method of claim 1 wherein the signal line is a synchronous optical networking (SONET) line.
6. (Original) An apparatus comprising:
  - a bus interface;
  - an ingress time slot interchange (ITSI) module;
  - a switch fabric coupled to the ITSI module;
  - an egress time slot interchange (ETSI) module having a plurality of inputs, each input assigned a logical identifier which remains fixed after initialization; and
  - a translation module to translate an incoming signal identifier to one of the logical identifiers independent of a physical line on which the signal is received.
7. (Original) The apparatus of claim 6 wherein the translation module comprises:
  - a cross connect table.
8. (Previously Presented) The apparatus of claim 6 further comprising:
  - a bus coupled to the bus interface;
  - a termination module coupled to the bus; and
  - a line interface having an optical to electrical (O/E) and electrical to optical (E/O) converter.
9. (Previously Presented) The apparatus of claim 6 wherein the apparatus is implemented on a backplane of a line card.

10. (Currently Amended) A machine-readable medium having instructions, ~~when executed by a machine, causes the machine~~ which when executed by a processor, cause the processor to perform a method, the method comprising:

fixing a logical identifier for a signal line at an input port of an egress time slot interchange (ETSI) of an egress interface of a line card of a network element,  
the ETSI having a plurality of input ports, each having a signal line;  
mapping via a translation module coupled to the ETSI a first physical identifier for a first physical signal line to the logical identifier; and  
the translation module remapping a second physical identifier for a second physical signal line to the logical identifier responsive to a line failure on the first physical signal line.

11. (Previously Presented) The machine-readable medium of claim 10, wherein mapping comprises writing to a cross connect table and wherein remapping comprises rewriting the cross connect table.

12. (Previously Presented) The machine-readable medium of claim 10, wherein the method further comprises switching a signal from a second physical signal line to a physical line corresponding to the logical identifier responsive to the remapping.

13. (Previously Presented) The machine-readable medium of claim 10, wherein fixing comprises:

assigning an identifier to each port of the egress interface during initialization; and

preventing change to the identifier after initialization.

14. (Previously Presented) The machine-readable medium of claim 10, wherein the signal line is a synchronous optical networking (SONET) line.